

2. SPECIFICATIONS AND TECHNICAL DATA

[DESIGNATION]

Item	Specification
Name	HONDA outboard motor GB40
Type	Forced air cooled single cylinder
Total displacement	170 CC (10.4 cu. in)

[ENGINE PERFORMANCE]

Item	Specification
Normal output	3.3 HP /3,600 rpm
Maximum output	4.5 HP /4,000 rpm
Type fuel	Gasoline
Starting system	Normal recoil starter
Ignition system	Flywheel magneto
Fuel tank capacity	4.4 liters (1.16 US. gal., 0.97 Imp. gal.)

[OUTBOARD MOTOR PERFORMANCE]

Item	Specification
Maximum speed	Single passenger boat, 20 km/h (12.5 mph) Two-passenger boat, 15 km/h (9.4 mph)
Fuel consumption	2.3 liters/h (0.6 US. gal./h 0.5 Imp. gal./h)
Maneuverability	
Right turn	360° steering angle
Left turn	360° steering angle
Engine lubricating system	Wet sump
Oil capacities	
Outboard drive unit	0.16 liters (0.35 US. pt., 0.27 Imp. pt.)
Engine	0.57 liters (1.2 US. pt., 1.0 Imp. pt.)
Propulsion	50 kg (110 lbs)